

# FUJI AUTO NOZZLE CLEANER II

## SPECIFICATIONS

|                    |  |
|--------------------|--|
| Item               |  |
| Applicable nozzles | NXT series, AIMEX series nozzles (H24, V12, H12, H12S, H12HS, H08, H08M, H04, G04, GL * <sup>1</sup> ), XPF series, XP series, CP-8 series, CP-7 series, CP-6 series nozzles |
| Nozzle diameters   | φ0.3 to φ1.3 mm  |
| Cleaning fluid     | Ultra-pure water (tank volume 1000 cc)Used amount: 50 * <sup>2</sup> cc/h  |
| Cleaning time:     | 1 second to 99 minutes 59 seconds (possible) (can change, recommended: 45 sec)   |
| Number of nozzles  | 1 to 48 (possible)   |
| Drying time        | 1 second to 99 minutes 59 seconds (possible) (can change, recommended: 15 sec)   |
| Size, weight       | 300 x 510 x 440 mm (width x depth x height), 35 kg   |
| Power supply       | AC 100 to 240 V  |
| Air supply         | Air pressure 0.5 MPa   |

\*1 Can clean the needles for GL heads.

\*2 When using the recommended pressure settings of 0.4 MPa for jet pressure and 0.45 MPa for solution supply pressure. If the pressure settings are changed, the quantity of solution used is changed also.

\*Contact Fuji or sales agents for specific operating conditions and detailed specifications.